

SAFETY REGULATIONS

1. Before starting any assembling operation of NORTHON couplings make sure that machines that will be connected can not start running in any way.
Verify that the power supply is off.
2. Assembling operations must be done exclusively by qualified and trained personnel.
3. Personnel that take part in the assembling operations must wear adequate clothes and should have personal safety devices.
4. The couplings are normally supplied with corrosion inhibitor for the internal warehousing.
When remove it, it is required to protect adequately both assembling personnel and the working environment.
5. The use of lifting equipment in order to position and assemble the coupling requires a complete respect of the safety rules.
6. In case of use of flames respect safety rules. Keep in mind that is prohibited to use flames in saturated environments with a high risk of explosions.
7. In any case of tampering or modification of the couplings from its original state, the constructor will not be liable for any kind of possible direct or indirect damage caused to people, animals or things.
8. During the first starting of the installation make sure that there are no safety risks for the personnel in charge of assembling. It is absolutely necessary to keep a certain safety distance from the point of the installation of the coupling.
9. The couplings, being rotating parts, are subject to the present EU industrial injury legislation that provides the use of the protection carter.
10. Finally, it is important to remember that the coupling should not exceed the values of the working torque, speed or angular misalignment indicated by the constructor.

This catalogue replaces every previous edition. TRANS-MOTO reserves the right to modify it without any prior notice. 2013 edition